



GALAXY STONE

EPOXY STONE FLOORING

INSTRUCTIONS FOR APPLYING Galaxy Stone SEALER

One Sealer Kit includes:

- 1 gallon jug containing epoxy resin called part "A"
- ½ gallon jug containing hardener called "B"

Not included:

- ½ Gallon of Zylene per 1 gallon of "A"
- About ½ of a cup of Medium size or Play sand for non-skid

This Kit should have coverage between 200-300 sq.ft. Depending on the thickness of the application.

The less zylene you use the thicker the product and quicker set time.

If resealing inside –Use Fans for ventilation—Acetone can be substituted for Zylene

*****BOTH ARE HIGHLY FLAMMABLE *****

INSTRUCTIONS FOR MIXING

Mix vigorously as follows:

1. One part "A" with ½ part Zylene for two (2) minutes
2. Blend in "B" with ½ the amount used of "A" to the previous mix.
Mix another two (2) minutes (Example): 1 gallon A to ½ gal Zylene then add ½ gallon B

***** NOTE: ---- You will have plenty of time to use this mix if you DO NOT PLAY AROUND. Remember, this is EPOXY.

*****WARNING:** It is **very important** that the area must be thoroughly DRY before Application. We recommend 48 hours since any contact with water. For a beautiful job, clean surface prior to applying sealer.

Just like painting, Start at one end and roll a 2-4 foot span going from one side to the other, slightly overlapping the previous row. You can apply your non-skid when finished if you can reach the entire area. Cast small handfuls of the non-skid like feeding chickens, Remember, you can keep adding a little more but you can't take it back if you cast too much all at once.

TOOLS NEEDED: Everything is available and CHEAP at any Dollar Store.

1 5-gallon bucket paint screen, 1 medium nap roller cover and roller cage. You can use a handle from a broom for an extension pole.

USE LACQUER THINNER FOR CLEAN UP or DISGUARD EVERYTHING

Latex Gloves recommended

PLEASE CALL IF UNSURE OF ANY PART OF THESE INSTRUCTIONS.

Pittsburgh Pa. 412-795-6056 9:00 am. ---- 5:00 pm. E.S.T.